

HIGHTEC BIO SKM

Readily biodegradable saw chain oil.

Description

HIGHTEC BIO SKM saw chain oil is recommended for lubricating chainsaws from reputable manufacturers.

Application

HIGHTEC BIO SKM has large power reserves that guarantee less wear and thus a longer service life for the chain, even under adverse operating conditions. The saw chain oil HIGHTEC BIO SKM retains the highest level of wear protection and its slightly thixotropic characteristics due to selected additives.

Advantages

- Excellent wear protection
- Adherent ('thixotropic')
- Suitable for all applications
- Not water-soluble
- Recommended for use throughout the year due to its optimal viscosity temperature behaviour



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.919
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	100
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	235
Biodegradability	OECD 301 B	%	>60

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH
Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle?
Scan this code for the ROWE-oilfinder.